

VERTICAL MAST LIFTS

VM05EL (VM160EL)

Compliant with CE/ANSI/CSA standards

HIGHLIGHTS

Efficient Construction

- Suitable for Indoor & Outdoor use
- Front wheel drive offers a small turning radius and anti-slip features
- Saloon style entry gate for ease of entry onto the platform

Reliable Performance

- Utilizes a pin-type weighing sensor, ensuring stable and accurate weighing unaffected by environmental factors
- Three level lifting cylinder drives lifting, simplifying transmission mechanism components by 70% and ensuring reliable lifting
- Automatic pothole protection system for better passability when mast is lowering

Convenient Maintenance

- Double fully-open doors design on chassis for easier access to the maintenance of all components
- Human-computer interaction interface, wide-screen display, fault self-diagnosis, intelligent and efficient
- AGM maintenance-free batteries come as standard, decrease total cost of ownership
- The core components control system, motor controller, battery and charger are common with Sinoboam scissor lifts, reducing operating costs



Standard Features

2WD×2WS	AGM maintenance-free battery	Fault diagnosis system
Solid non-marking tires	Proportional control	Emergency lowering system
Emergency stop	Electrophoretic painting	Tilt protection system
Flashing beacon	Lifting and tie-down points	Overload sensing system
Drivable at full height	Automatic pothole protection	Manual storage box
Horn & buzzer	Bumper rails	Auto braking system
Telematics-ready connector	Cylinder mast system	

Options & Accessories

Tool tray		
-----------	--	--

SINOBOOM™

PARTNERS IN ACCESS™

SINOBOOM.COM | SALES@SINOBOOM.COM

NO.128 EAST JINZHOU AV., NINGXIANG HI-TECH INDUSTRY PARK, CHANGSHA, HUNAN, CHINA, 410600

VERTICAL MAST LIFTS

VM05EL (VM160EL)

Compliant with CE/ANSI/CSA standards

Model	VM05EL (VM160EL)
Dimensions	
Max Working Height (Indoor/Outdoor)	6.9 m (22'7.7") / 5.7 m (18'8.4")
A Max Platform Height (Indoor/Outdoor)	4.9 m (16'1") / 3.7 m (12'1.7")
Max Horizontal Reach	0.5 m (1'7.7")
B Length-stowed	1.38m (4'6.3")
C Overall Width	0.78 m (2'6.7")
D Height-stowed	1.99 m (6'6.3")
E Wheelbase	1.06 m (3'5.7")
Axle-base	0.67 m (2.2')
Ground Clearance (Pothole Guard Stowed)	0.068 m (2.7")
Ground Clearance (Pothole Guard Deployed)	0.015 m (0.59")
Platform Size (L×W×H)	1.34 m×0.74 m×1.1 m (4'5"×2'5"×3'7")
Performance	
Platform Capacity	227 kg (500 lbs)
Extension Platform Capacity	113 kg (249 lbs)
Max Platform Occupants (Indoor/Outdoor)	1 Person/1 Person
Drive Speed (Stowed)	0~4 km/h (0~2.5 mph)
Drive Speed (Raised)	0~0.5 km/h (0~0.3 mph)
Lift Time (Rated load)	24~28s
Lower Time (Rated load)	24~28s
Gradeability (2WD)	25%
Max Allowable Inclination (Front-To-Back/Side-To-Side)	3°/1.5°
Turning Radius (Inside/Outside)	0.14 m/1.34 m (5.5"/4'5")
Tire Size/Type	305×100 mm (12×4") / solid 305×114 mm (12×4.5") / solid
Power	
Drive×Steer	2 WD×2 WS
Power Source (V/kW)	24 V DC, 2.2 kW
Hydraulic Tank Capacity	6 L (1.3 gal (UK))/1.6 gal (US))
Battery	24 V, 120 Ah
Charger (Input/Output)	100~240 V AC/15A
Weight	
Weight (Indoor)	970 kg (2,138 lbs)
Standards Compliance	CE/ANSI/CSA

