

AXOLIFT: Offering smart and safe alternatives to ladders

ELIFT 3.0: SELF-PROPELLED MAST LIFT

Up to 4,95 meters in total safety

www.gbhw.nl

- Full electric
- Zero emission and environmentally friendly
- Hydraulic oil collector in case of leakage
- Low cost maintenance
- Easy access to maintenance

ELIFT 3.0 platform is a full electric, versatile, robust and simple to use vertical mast lift platform, ideal for many applications – from construction to industries.

- Hydraulically powered descent
- Integrated battery charger
- Easy to operate when lowered and raised
- Forkliftable
- Rubber protection around the machine.

SAFETY:

Automatic entry gates.

Foot brake on rear wheels.

Tilt alarm.

Emergency lowering at chassis controls.

Automatic breaking system.

Attachment point.

ELIFT 3.0 technical data

Dimension:

Max. Working Height:	4,95 m
Max. Platform Height:	2,95 m
Overall Width:	765 mm
Overall Length:	1215 mm
Stowed Height:	1765 mm
Work Platform:	890X 645 mm
Ground Clearance:	35 mm

Performance:

Platform Capacity SWL:	180kg / 1 pers.
Tool Tray Capacity:	20 kg
Raise/ Lower Time:	17 Sec.
Allowable Cant:	0° - Internal Use
Max. Wind Speed:	0km/h- Internal Use
High resistance paint Orange RAL 2000	
Marking and conformity CE- Compliance with the standard EN 280	

Power:

Power Source:	24 Volt DC Battery
Charger:	24V- 11A

Weight:

Gross Weight:	380 kg
---------------	--------



GB Hoogwerkers B.V.

Tenorweg 16, 3363LN Sliedrecht Nederland

T +31 10 200 2083

➤ info@gbhw.nl

➤ www.gbhw.nl

